

DXi.A

DIRECT EXPANSION CLOSE CONTROL UNIT AIR-CONDENSED WITH INVERTER COMPRESSOR

R410a



Close control air-conditioners for vertical installations and cooling only, with optional heating by means of heating element, optional humidifier and dehumidifier for precise temperature and humidity control.

Particularly suitable for precision air conditioning in servers and IT rooms and all technological applications in general. The INVERTER compressor allows the cooling capacity modulation according to the real internal load, particularly efficient at the partial loads, optimizing the power absorbed and eliminating the starting current. Electronic expansion valve and EC Inverter fans are fitted in this model as standard. External air condenser. Emibyte equipment are fully designed and tested in the Emicon validation laboratories.

Features

Unit for installing inside or outside the room to be air-conditioned. Maximum resistance to rust thanks to the galvanized sheet metal structures and panels with bevelled corner uprights to enhance its unique, clean and attractive design. The panels are lined with sound-insulating material to limit noise levels. Last generation of BLDC INVERTER compressor designed to deliver maximum cooling efficiency when you need it most. This latest variable speed compressor technology allows CRAC system manufacturers as Emicon to achieve superior performance. New generation EC Inverter centrifugal fan made in high class technological material with 5 backward curved blades. Impeller with bionic 3D profile thanks to an innovative design in the form of a blade geometry with specific buckling. Special V-shaped rear edge allows a wide characteristic field. Together with the rotating diffuser that opens, exceptional performances of the impeller and the entire system are thus obtained. In combination with the undulated surface of the blade surface, a diffused sound emission takes place which guarantees a very low noise level.

Standard COARSE 60% (ISO EN 16890) EU4/G4 filtering section is fitted. The filter is self-extinguishing. The microprocessor controls the compressor activation times thereby regulating the cooling capacity; it also controls the operating alarms with the possibility of interfacing to supervisor and remote-servicing systems.

Refrigerant circuit consisting of Electronic Expansion Valve, sight glass filter dryer on liquid line, pressure transducer with indication, control and protection functions on low and high refrigerant pressure, high pressure safety switch with manual reset, liquid receiver with accessories

Control

Semi-graphic display 132x64 pixel, programmable software, record storage of 200 alarms, general alarm, automatic reset after blackout, integral LAN system, standby management, automatic rotation, serious alarms, operating contemporaneousness, clock function modality.

VERSIONS

- D** - Downflow air supply
- U** - Up flow air supply
- E** - Front supply (Displacement)
- B** - Up supply, Rear return
- V** - Up supply (Down suction)

ACCESSORIES

- Remote user terminal
- Electric Heating coil
- Humidifier
- Vibration isolation frame with rubber mountings
- Interface electronic board
- Air distribution plenum
- Condensing pump discharge
- Interface card for TCP/IP Protocol
- Longwork, motbus, bacnet
- Touch screen graphic terminal
- Power supply different from standard

TECHNICAL DATA

DXi.A		61	111	121	151	181	201	251	321
Cooling capacity (Total) ⁽¹⁾ ESP 20 Pa	kW	7,2	10,1	11,2	16,1	18,2	20,5	25,6	33,7
Cooling capacity (Sensible) ⁽¹⁾ ESP 20 Pa	kW	7,2	9,3	11,2	14,5	17,6	20,5	25,5	30,7
Tot. absorbed power ⁽²⁾ ESP 20 Pa	kW	2,3	3,5	3,7	4,6	5,1	5,3	7,2	8,6
SHR		1,00	0,92	1,00	0,91	0,97	1,00	1,00	0,91
Air flow	m ³ /h	3900	3900	3900	3900	5700	5700	8150	8150
Fan	n°	1	1	1	1	1	1	1	1
Max. ESP	Pa	559	560	479	412	568	539	451	362
Unit EER without remote condenser to max. frequency	W/W	3,23	2,87	3,01	3,49	3,57	3,84	3,53	3,91
Maximum absorbed power	Kw	4	6	6	9	11	11	12	15
Maximum absorbed current	A	14	18	18	16	21	21	21	24
Starting current	A	4	4	4	4	7	7	6	6
Power supply	V/ph/Hz	400/3/50+N+PE							
Humidifier									
Steam production (nominal)	kg/h	3	3	3	3	5	5	8	8
Steam production (max.)	kg/h	3	3	3	3	8	8	8	8
Max. absorbed power	kW	2,25	2,25	2,25	2,25	3,75	3,75	6,0	6,0
Max. absorbed current	A	10,0	10,0	10,0	10,0	5,5	5,5	8,7	8,7
Specific conductivity at 20°C (min/max)	µS/cm	300/1250	300/1250	300/1250	300/1250	300/1250	300/1250	300/1250	300/1250
Total hardness (min/max)	mg/l CaCO ₃	100/400	100/400	100/400	100/400	100/400	100/400	100/400	100/400
Electrical heaters									
Steps	n°	3	3	3	3	2	2	3	3
Power	kW	4,5	4,5	4,5	4,5	6,0	6,0	9,0	9,0
Absorbed current	A	6,5	6,5	6,5	6,5	8,7	8,7	13,0	13,0
Oversized electrical heaters									
Steps	n°	2	2	2	2	3	3	3	3
Power	kW	6,0	6,0	6,0	6,0	9,0	9,0	12,0	12,0
Absorbed current	A	8,7	8,7	8,7	8,7	13,0	13,0	17,3	17,3
Hot water coil									
Heating capacity ⁽³⁾	kW	7,3	7,3	7,3	7,3	10,6	10,6	16,7	16,7
Water flow	m ³ /h	1,3	1,3	1,3	1,3	1,8	1,8	2,9	2,91
Pressure drop (coil + 3 way valve)	kPa	31	31	31	31	48	48	56	56
Coil internal volume	dm ³	1,4	1,4	1,4	1,4	2,1	2,1	3,3	3,3
Compressors									
Circuits / Compressors	n°/n°	1/1	1/1	1/1	1/1	1/1	1/1	1/1	1/1
On / Off Compressors	n°	--	--	--	--	--	--	--	--
Inverter Compressors	n°	1	1	1	1	1	1	1	1
Condensing water pump									
Nominal flow	l/h	390,0	390,0	390,0	390,0	390,0	390,0	390,0	390,0
Max. flow (prevalence = 0 m)	l/h	500	500	500	500	500	500	500	500
Max. discharge height (flow=0 m ³ /h)	m	5,4	5,4	5,4	5,4	5,4	5,4	5,4	5,4
Condensing water pump + humidifier									
Nominal flow	l/h	-	-	-	-	-	-	600	600
Max. flow (prevalence = 0 m)	l/h	-	-	-	-	-	-	900	900
Max. discharge height (flow=0 m ³ /h)	m	-	-	-	-	-	-	6,0	6,0
Dimensions and weight									
Frame	n°	2	2	2	2	3	3	4	4
Width	mm	750	750	750	750	980	980	1160	1160
Depth	mm	550	550	550	550	750	750	850	850
Height	mm	1980	1980	1980	1980	1980	1980	1980	1980
Weight (Configuration U)	Kg	198	205	209	219	284	292	331	362
Weight (Configuration V)	Kg	201	208	212	222	288	296	336	367
Weight (Configuration D)	Kg	203	209	213	223	290	298	338	369
Weight (Configuration B)	Kg	201	208	212	222	288	296	336	367

(1) Ambient temperature 24°C, Relative humidity 50%, Condensing temperature 48°C. (3) Water temperature 40/45°C, Ambient temperature 20°C, Relative humidity 50%.

(2) The fans electrical power has to be added to the ambient load.

DX.A		381	392	472	491	531	532	631	652
Cooling capacity (Total) ⁽¹⁾ ESP 20 Pa	kW	37,2	39,0	47,4	50,7	54,0	52,8	64,8	68,4
Cooling capacity (Sensible) ⁽¹⁾ ESP 20 Pa	kW	37,1	38,9	44,3	45,1	52,7	52,7	63,4	64,6
Tot. absorbed power ⁽²⁾ ESP 20 Pa	kW	10,1	10,5	13,4	13,9	14,1	14,6	16,7	17,5
SHR		1,00	1,00	0,93	0,89	0,97	1,00	0,98	0,95
Air flow	m ³ /h	11500	11500	11500	11500	14500	14500	17600	17600
Fan	n°	1	1	1	1	2	2	2	2
Max. ESP	Pa	428	427	402	388	417	432	417	392
Unit EER without remote condenser to max. frequency	W/W	3,70	3,72	3,54	3,65	3,83	3,63	3,87	3,91
Maximum absorbed power	Kw	16	19	21	23	24	23	28	31
Maximum absorbed current	A	26	38	40	34	37	42	47	48
Starting current	A	8	24	25	8	10	27	156	30
Power supply	V/ph/Hz	400/3/50+N+PE							
Humidifier									
Steam production (nominal)	kg/h	8	8	8	8	8	8	8	8
Steam production (max.)	kg/h	8	8	8	8	8	8	8	8
Max. absorbed power	kW	6,0	6,0	6,0	6,0	6,0	6,0	6,0	6,0
Max. absorbed current	A	8,7	8,7	8,7	8,7	8,7	8,7	8,7	8,7
Specific conductivity at 20°C (min/max)	µS/cm	300/1250	300/1250	300/1250	300/1250	300/1250	300/1250	300/1250	300/1250
Total hardness (min/max)	mg/l CaCO ₃	100/400	100/400	100/400	100/400	100/400	100/400	100/400	100/400
Electrical heaters									
Steps	n°	3	3	3	3	3	3	3	3
Power	kW	9,0	9,0	9,0	9,0	15,0	15,0	18,0	18,0
Absorbed current	A	13,0	13,0	13,0	13,0	21,7	21,7	26,0	26,0
Oversized electrical heaters									
Steps	n°	3	3	3	3	3	3	3	3
Power	kW	12,0	12,0	12,0	12,0	18,0	18,0	24,0	24,0
Absorbed current	A	17,3	17,3	17,3	17,3	26,0	26,0	34,6	34,6
Hot water coil									
Heating capacity ⁽³⁾	kW	24,5	24,5	24,5	24,5	31,1	31,1	37,4	37,4
Water flow	m ³ /h	4,3	4,3	4,3	4,3	5,43	5,43	6,5	6,5
Pressure drop (coil + 3 way valve)	kPa	46	46	46	46	53	53	34	34
Coil internal volume	dm ³	4,7	4,7	4,7	4,7	5,8	5,8	7,1	7,1
Compressors									
Circuits / Compressors	n°/n°	1/1	2/2	2/2	1/1	1/1	2/2	1/2	2/2
On / Off Compressors	n°	--	--	--	--	--	--	1	--
Inverter Compressors	n°	1	2	2	1	1	2	1	2
Condensing water pump									
Nominal flow	l/h	390,0	390,0	390,0	390,0	390,0	390,0	390,0	390,0
Max. flow (prevalence = 0 m)	l/h	500	500	500	500	500	500	500	500
Max. discharge height (flow=0 m ³ /h)	m	5,4	5,4	5,4	5,4	5,4	5,4	5,4	5,4
Condensing water pump + humidifier									
Nominal flow	l/h	600	600	600	600	600	600	600	600
Max. flow (prevalence = 0 m)	l/h	900	900	900	900	900	900	900	900
Max. discharge height (flow=0 m ³ /h)	m	6,0	6,0	6,0	6,0	6,0	6,0	6,0	6,0
Dimensions and weight									
Frame	n°	4,5	4,5	4,5	4,5	5	5	6	6
Width	mm	1505	1505	1505	1505	1860	1860	2210	2210
Depth	mm	850	850	850	850	850	850	850	850
Height	mm	1980	1980	1980	1980	1980	1980	1980	1980
Weight (Configuration U)	Kg	416	433	435	419	509	525	606	620
Weight (Configuration V)	Kg	421	439	441	425	516	531	614	627
Weight (Configuration D)	Kg	424	442	443	428	519	535	617	631
Weight (Configuration B)	Kg	421	439	441	425	516	531	614	627

(1) Ambient temperature 24°C, Relative humidity 50%, Condensing temperature 48°C. (3) Water temperature 40/45°C, Ambient temperature 20°C, Relative humidity 50%.

(2) The fans electrical power has to be added to the ambient load.

DXi.A		691	742	761	861	931	952	1021	1142
Cooling capacity (Total) ⁽¹⁾ ESP 20 Pa	kW	70,1	74,9	78,2	85,8	94,7	96,5	100,7	109,8
Cooling capacity (Sensible) ⁽¹⁾ ESP 20 Pa	kW	66,3	74,7	75,2	80,2	91,6	93,9	96,1	98,8
Tot. absorbed power ⁽²⁾ ESP 20 Pa	kW	18,8	19,9	20,2	23,7	24	25,9	27,6	30,8
SHR		0,95	1,00	0,96	0,94	0,97	0,97	0,95	0,90
Air flow	m ³ /h	17600	20900	20900	20900	25700	25700	25700	25700
Fan	n°	2	2	2	2	3	3	3	3
Max. ESP	Pa	432	437	436	429	446	449	442	431
Unit EER without remote condenser to max. frequency	W/W	3,73	3,76	3,88	3,62	3,95	3,73	3,65	3,57
Maximum absorbed power	Kw	30	33	36	38	45	49	47	56
Maximum absorbed current	A	50	51	58	61	76	74	79	93
Starting current	A	167	33	168	179	185	47	219	203
Power supply	V/ph/Hz	400/3/50+N+PE							
Humidifier									
Steam production (nominal)	kg/h	8	8	8	8	8	8	8	8
Steam production (max.)	kg/h	8	8	8	8	8	8	8	8
Max. absorbed power	kW	6,0	6,0	6,0	6,0	6,0	6,0	6,0	6,0
Max. absorbed current	A	8,7	8,7	8,7	8,7	8,7	8,7	8,7	8,7
Specific conductivity at 20°C (min/max)	µS/cm	300/1250	300/1250	300/1250	300/1250	300/1250	300/1250	300/1250	300/1250
Total hardness (min/max)	mg/l CaCO ₃	100/400	100/400	100/400	100/400	100/400	100/400	100/400	100/400
Electrical heaters									
Steps	n°	3	3	3	3	3	3	3	3
Power	kW	18,0	24,0	24,0	24,0	27,0	27,0	27,0	27,0
Absorbed current	A	26,0	34,6	34,6	34,6	39,0	39,0	39,0	39,0
Oversized electrical heaters									
Steps	n°	3	3	3	3	3	3	3	3
Power	kW	24,0	27,0	27,0	27,0	36,0	36,0	36,0	36,0
Absorbed current	A	34,6	39,0	39,0	39,0	52,0	52,0	52,0	52,0
Hot water coil									
Heating capacity ⁽³⁾	kW	37,4	48,9	48,9	48,9	60,8	60,8	60,8	60,8
Water flow	m ³ /h	6,5	8,5	8,5	8,5	10,6	10,6	10,6	10,6
Pressure drop (coil + 3 way valve)	kPa	34	48	48	48	42	42	42	42
Coil internal volume	dm ³	7,1	10,45	10,45	10,45	12,6	12,6	12,6	12,6
Compressors									
Circuits / Compressors	n°/n°	1/2	2/2	1/2	1/2	1/2	2/2	1/2	2/4
On / Off Compressors	n°	1	--	1	1	1	--	1	2
Inverter Compressors	n°	1	2	1	1	1	2	1	2
Condensing water pump									
Nominal flow	l/h	390,0	390,0	390,0	390,0	390,0	390,0	390,0	390,0
Max. flow (prevalence = 0 m)	l/h	500	500	500	500	500	500	500	500
Max. discharge height (flow=0 m ³ /h)	m	5,4	5,4	5,4	5,4	5,4	5,4	5,4	5,4
Condensing water pump + humidifier									
Nominal flow	l/h	600	600	600	600	600	600	600	600
Max. flow (prevalence = 0 m)	l/h	900	900	900	900	900	900	900	900
Max. discharge height (flow=0 m ³ /h)	m	6,0	6,0	6,0	6,0	6,0	6,0	6,0	6,0
Dimensions and weight									
Frame	n°	6	7	7	7	8	8	8	8
Width	mm	2210	2565	2565	2565	3100	3100	3100	3100
Depth	mm	850	850	850	850	850	850	850	850
Height	mm	1980	1980	1980	1980	1980	1980	1980	1980
Weight (Configuration U)	Kg	606	717	710	710	869	878	869	954
Weight (Configuration V)	Kg	614	725	719	719	880	888	880	965
Weight (Configuration D)	Kg	617	729	723	723	885	893	885	970
Weight (Configuration B)	Kg	614	725	719	719	880	888	880	965

(1) Ambient temperature 24°C, Relative humidity 50%, Condensing temperature 48°C. (3) Water temperature 40/45°C, Ambient temperature 20°C, Relative humidity 50%.

(2) The fans electrical power has to be added to the ambient load.