

Technical Specification

[illegible]

Humidifying capacity (Standard)	Kg/h	6	8	8	10	10	10	10	10	10	12	12	12
Humidifying capacity (Max)	Kg/h	8	8	8	15	15	15	15	15	15	15	15	15
Number of compressors	Pcs	1	1	1	1	1	2	2	2	2	2	2	2
Number of fan	Pcs	1	1	1	2	2	2	2	2	2	3	3	3
Full-load Current (Air cooled and chilled water)	A	28.8	32.7	35.1	48.3	54.4	48.3	53.6	58.7	63.5	76.3	81.7	96.6
Full-load Current (Water cooled and chilled water)	A	26.1	27.3	29.7	42.9	49	38.4	48.2	50.6	55.4	68.2	73.6	85.8
Size of inlet and outlet water pipes	mm	28	28	35	35	35	35	35	35	35	42	42	42
Unit Weight	kg	400	470	480	640	650	700	730	800	810	1020	1040	1140
Unit Width	mm	850	1200	1200	1650	1650	1650	1650	2010	2010	2460	2460	2810
Unit Depth	mm	850	850	850	850	850	850	850	850	850	850	850	850
Unit Height	mm	1960	1960	1960	1960	1960	1960	1960	1960	1960	1960	1960	1960

Note :

● Parameter table

Air/water cooled unit data based on 24°C, 50%RH indoor return air temperature.

Chilled water unit data based on 24°C, 50%RH indoor return air temperature。The inlet and outlet water temperature of chilled water are 7°C and 12°C。

Electirc heating adopts three-level hierarchical control

●The power supply type: 380`415V/3p/50Hz

●We can provide other customized product.If you need more information,please contact us.

●Specifications are subject to change without prior notice